



SEDA FPCS - FIRE PROTECTION CAMERA SYSTEM

A-527879

BENEFITS

- Continuous automated monitoring and early detection of thermal hotspots
- Acoustic and visual early warning
- Automatic recording of critical events

MORE INFORMATION

- Product video
- More images
- Additional technical specifications
- Online configurator



Secure thermal imaging camera monitoring of critical lithium-ion storage systems



System Components:

- Thermal IP Camera
- Control Cabinet with a 23.8" monitor, NVR recorder, PoE network switch, Siemens compact controller, operational indicator light, acknowledgment button, and break-glass button for manual activation
- 6 m RJ45- Network cable
- Preconfigured for:
Fire alarm system
Exhaust system
Company network



Ideally combinable with the SEDA dismantling table or for monitoring the storage of HV batteries.

TECHNICAL SPECIFICATIONS

Dimensions	600 x 600 x 350 mm
Power supply	230 V / 50 Hz 13 A
Camera supply	PoE
Trigger temperature	68° C
Signal tone	98 dB

ORDER NUMBER

A-527879 SEDA Fire Protection Camera System

SEDA-Umwelttechnik GmbH

Schwendter Str. 10 / 6345 Kössen / Tirol / Austria
VAT-ID.: ATU56621622 / FB-Nr.: FN 231790 v / FB-Gericht: Innsbruck
Certified company according to DIN EN ISO 9001

T: +43 5375 6318-0
E: info@seda-international.com
W: www.seda-international.com

