



SEDA GAS TORCH

A-34002-V19

MORE INFORMATION

- Product video
- More images
- Additional technical specifications
- Online configurator



BENEFITS

- Safe disposal of liquefied petroleum gas
- Easy handling
- Comprehensive accessories



Safe tank draining for liquefied petroleum gas (LPG / propane)

Special version for draining LPG / propane tanks. Flaring should only be performed after safe recovery of the gas / propane, the burner to deal with the remaining fumes.

Recovery of propane from containers from vehicles (aka LPG tanks), should always be done by suction and flaring off any excess in a designated area and with the correct equipment.

Accessories & Equipment:

- LPG high-pressure hose (Length: 8 m) for connection to the torch
- Liquid phase regulator (58 psi)
- Telescopic stand with a maximum height of 8.2 ft
- Shut-off ball valve
- Piezo igniter (with refillable cartridge)
- Frost-resistant leak detection spray (13.5 oz)
- Cold-resistant gloves
- Adapter set



Accessories

TECHNICAL SPECIFICATIONS

Power	up to 250 kW/h
Usable height	up to 2,5 m

ORDER NUMBER

A-34002-V19	SEDA Torch
A-340109	Adapter set



SEDA Environmental LLC

135 Walter Way,
Fayetteville, GA 30214

T: +1 770 681 0474
E: bruce@seda-usa.com
W: www.seda-usa.com